


MCD1100 c d p l a y e r

- More than a simple CD player, the MCD1100 will play CD/SACD/MP3/WMA disks at the highest possible fidelity which yields maximum musical enjoyment. Five additional digital inputs and outputs are available allowing the use of many consumer and professional digital devices.
- A MAC or PC may be connected through the dedicated USB input for superior playback of stored music using any of the popular music management programs.
- High performance, variable volume, balanced outputs will run any power amplifier directly or may be used with the built in headphone amplifier for private listening.
- Die Cast aluminum transport and drawer assembly delivers quiet operation, precise handling of disks and long operational life.
- Classic glass faceplate design and polished stainless steel chassis are beautiful to see while adding long term value.



Highest possible fidelity yields maximum musical enjoyment.

McIntosh[®]

LEGENDARY PERFORMANCE™

www.mcintoshlabs.com

MCD1100 cd player

Disc Formats

SACD, CD, MP3, WMA

Number of Channels

2

Analog Audio Outputs

20Hz to 20kHz

Total Harmonic Distortion

2VRMS (Fixed Unbalanced)

4VRMS (Fixed Balanced)

6VRMS (Variable Unbalanced)

12VRMS (Variable Balanced)

Frequency Response

SACD 4Hz-40kHz -2dB+/-0.5dB

CD 4Hz-20kHz +/-0.5dB

S/N Ratio

110dB

Dynamic Range

100dB

Total Harmonic Distortion

SACD 0.0015%

CD 0.0015%

Digital Audio Outputs (CD Audio only)

Format: SPDIF

Optical: TOS Link, -15~-21dBm

Coaxial: RCA Jack, 0.5V p-p @ 75ohms

XLR: XLR Connector, 5V p-p @ 110 ohms

BNC: BNC Connector, 0.5V p-p @ 75ohms

Sampling Frequencies: 44.1kHz (PCM)

Digital Audio Inputs (CD Audio only)

Format: SPDIF

Optical: TOS Link, -15~-21dBm

Coaxial: RCA Jack, 0.5V p-p @ 75 ohms

XLR: XLR Connector, 5V p-p @ 110 ohms

BNC: BNC Connector, 0.5V p-p @ 75 ohms

USB: USB Type B Connector

Sampling Frequencies: Up to 192kHz,

24Bit for Optical and USB inputs

Overall Dimensions

Width 17-1/2" (44.5cm)

Depth 19" (48.3cm) including handles

Height 9-7/16" (24cm) including feet

Weight

28.2 pounds (12.79kg) net, 44.6 pounds

(20.23kg) in shipping carton



R-Core Power Transformer

The special construction of the R-Core power transformer minimizes noise and hum radiation.

Variable Balanced and Unbalanced Audio Outputs

Balanced for long cable runs in a noisy environment and unbalanced for short runs. Balanced offers optimum noise rejection. The maximum output level is 6Vrms which allows direct drive of power amplifiers without need for preamplifier.

Phase-Locked Loop Internal Clock Generation

Clocks are generated by Phase-Locked Loop generator for a stable and low jitter operation.

For the Consumer's Protection:

In order to ensure the highest level of customer satisfaction, "new" McIntosh products may only be purchased over-the-counter or delivered and installed by an Authorized McIntosh Dealer. McIntosh products that are purchased over the Internet, by phone or mail order are presumed to be "used" and do not qualify for any McIntosh Warranty. McIntosh does not warrant, in any way, products that are purchased from anyone who is not an Authorized Dealer or products that have had their serial number altered or defaced.

NEED NEW IMAGE
HERE

Companion Products

The McIntosh C1000 Preamplifier, MC601 Power Amplifier and the XR200 Loudspeaker are logical companions for the MCD1100 CD Player. Your Authorized Dealer can provide additional information on other McIntosh product combinations.

To experience the legendary performance of McIntosh, please call on us at 1.800.538.6576.

McIntosh®

LEGENDARY PERFORMANCE™